

Radio functions	●	GSM/GPRS/EDGE(2.5G) Band(850/900/1800/1900MHz) GPRS class 10 Type B wifi 802.11b/g
Services	●	Speech Services with EFR/FR/AMR codec Emergency call DTMF tone generation Call holding, waiting, forwarding, barring SMS
SIM function	●	3V/1.8V uSIM operation SIM application toolkit
Chipset	●	SAMSUNG SC32442B 32 bit RISC 400MHz
OS	●	Microsoft® Windows Mobile® 6.1
LCD	●	2.8" Touch-panel, 320x240 resolution 256k color TFT
2D Image Engine	●	"MaxiCode, Data Matrix, PDF417, Code39, UPC, QR Code, OCR A"
Memory	●	64MByte SDRAM + 128MByte FLASH
Antenna	●	External
Audio Frequency	●	record and play audio Stereo
Keyboard/ Buttons	●	Power button Send and End buttons Two (2) soft-keys 5-way navigation Soft reset 12-KEY numeric Key
Notification	●	2 LED(three color light), sound, and vibration notification Green / Red LED indicates network status, device power, charging status and system event notification
Connectivity	●	Class 2 transmit power Supported profiles ActiveSync profile Generic Access profile Serial Port profile Object Push / OBEX profile DUN (dial-up networking profile) Hands-free profile
Interface	●	USB 1.1 connection and power charging SIM card slot T-flash card slot infrared slot USB supports OTG standard. Serial port
Bar Code scanner	●	Yes(HHP 2D imager 0.3 MEGA Pixels)
IC card reader/writer	●	Yes
Infrared Gate	●	Yes
RFID Module	●	Yes(optional)
BLUETOOTH / WIFI	●	Yes (either one)
GPS Module	●	No
Battery	●	2000mAH Removable and chargeable Li-Ion Meeting LTK 3 DoU professional
USB line	●	Yes
Charger	●	Yes (support battery charger, car charger)
"Communication Software"	●	phone/SMS/SMS extension slot
Network Software	●	E-mail/Browser/MSN messenger
Multi-media Software	●	Record Media Player
Office Software	●	Address list Calendar sticky notes Calculator Notes book
Document viewer	●	PDF/Excel/Word/Power Point/Picture
Expansion Function Module drive	●	bar-code scanner driver IC card reader driver
Other software	●	customize
Drop	●	1.5 m
IP	●	IP 65
Weight	●	223g including battery
Dimension	●	136 mm(L)× 75 mm(W) × 27 mm (H)
Operating Temperature	●	From - 20 °C to + 65 °C

VIC COMPUTER (HK) CO., LTD.

域士電腦(香港)有限公司

Tel: +852 8206 1828

Fax: +852 2725 0766

Email: Sales@VIC.HK

http: // VIC.HK