

DNP

CX-320

RE-TRANSFER CARD PRINTER



Innovative

ID card with finest photo quality

Solution



CX-320


DNP CX-320 re-transfer card printer

CX-320

Upgrade from DNP CX210

- High-speed USB 2.0 connection
- Improve the algorithm of data processing speed contributes to shorten the total printing time
- Printer is operative under network (LAN) environment
- Adopt smarter printer driver which facilitates contact/contactless IC encoding
- Adopt intelligent ink ribbon manufactured by DNP which works with SMP (Status Monitor Program) to look over various status of the printer from PC
- Expand the range of print setting to print various type of card
- Improve the reliability of the printer
- RoHS Compliant

CL-500D



Re-Transfer printing process
(The illustration is for explanation purpose only.)



Card hopper holds up to 300 cards(0.76mm)



CX211CSD is a compact case designed to mount contactless encoding module inside and it is easy to attach to CX-320



CX-320 Re-transfer card printer



CL-500D is a field-upgradable lamination unit which works with CX-320 perfectly

Ongoing feature of DNP CX210

- Perfect edge to edge printing with the highest speed 125 cards/hour
- Glossy photo finish quality (No pre-printing required)
- Ideal for contact chip & RFID card desktop personalization
- Versatile print capability for card materials (PVC, PET, ABS, Polycarbonate etc.)
- Printhead free from damaged by card
- Parallel operation of printing and encoding save the total time
- Meet requirements for various encode/print needs

● Specification

Printing Method	Dye Sublimation/Resin Thermal transfer
Resolution	300 dpi
Printable Area	Full-Bleed
Print Speed	29 seconds/card
Interface	USB2.0
Dimension	W343 x H381 x D339mm
Weight	22kg
Signal Level	256 levels per color (YMC) 2 levels (Bk)
Hopper Capacity	300 cards (0.76mm thickness)
Stocker Capacity	100 cards (0.76mm thickness)
Ink ribbon	YMCK ink ribbon set (1,000 cards(single side)), YMCKK ink ribbon set (1,500 cards(4c x 1c))
Options	Magnetic Stripe Encoding / IC Encoding / Contactless Encoding Lamination unit (CL-500D)
Safety Standard	UL, VCCI-B, FCC Class B, EN Class B

VIC COMPUTER (HK) CO., LTD.
域士電腦(香港)有限公司

Tel: (852) 2725 1612

Fax: (852) 2725 0766

Email: Sales@VIC.HK

http://VIC.HK